


FLUSH SLATE

Flat Vent Profile

- Low profile - high throughput
- Integral insect screening
- Cut to match slate size
- Easy regulation compliance



Solution

The Flush Slate Ventilator offers an almost flat external presence and may be used to directly ventilate the roof space or utilising an optional connection kit may be linked to a 110mm outlet pipe servicing bathroom air extraction. Minimum rafter pitch: 22.5° or 25° depending on head lap.

Bill of Quantity / Specification Wording

Clause 900 G20 carpentry


Slate Ventilator Type Contract / Flush (state) by Cavity Trays of Yeovil Somerset, BA22 8HU (01935 474769). Number _____.

Product name	Flush Slate Roof Ventilator
Size (2)	600 x 300mm and 500mm x 250mm
Free airflow rating	Max 10,000mm ² at appropriate centres
Colour	Black - Grey
Material	Polypropylene
Observations	Cut to match slate size. Integral insect grille

CONTRACT SLATE

Raised Vent Profile

- Low profile - high throughput
- Integral insect screening
- Cut to match slate size
- Easy regulation compliance



Solution

The Contract Slate Ventilator can be readily cut to suit both natural and man-made slates. This single model may be used with either 600 x 300mm or 500 x 250mm slates. The Contract Slate Ventilator may also be employed to facilitate natural non-mechanical extraction and ventilation. This is achieved using the Contract Connector Kit CS/HD that permits connection with a 110mm soil vent outlet. The airflow rating when this kit is attached is 8,000mm². Minimum rafter pitch: 22.5° or 25° depending on head lap.

Bill of Quantity / Specification Wording

Clause 900 G20 carpentry

Slate Ventilator Type Contract / Flush (state) by Cavity Trays of Yeovil Somerset, BA22 8HU (01935 474769). Number _____.

Product name	Contract Slate Roof Ventilator
Size	600 x 300mm
Free airflow rating	Max 10,000mm ² at appropriate centres
Colour	Black - Grey
Material	Polypropylene
Observations	Cut to suit 600 x 300 or 500 x 250 slate size. Integral insect grille